

# ARCTURUS RECESSED UPLIGHT



## Technical Specification

Wattage:	6W
Light Source:	CREE
Lumens Output:	360lm
CCT:	2700K
Input Voltage:	AC 220-240V 50-60Hz
Beam Angle:	10x40°
Color Rendering Index:	CRI>90
McAdam:	Step 3-5
Ambient Temperature (Ta):	Step 3-5
IK Rating	IK09
Ingress Protection:	IP67
LED Lifespan:	>50,000hrs

## Luminaire Specification

Installation type:	Recess-mount
Body Material:	Die-cast Aluminum
Surface Material:	316L Stainless Steel
Light Window:	Clear Tempered Glass
Recessed Sleeve:	ABS Black Plastic


**Arcturus** recessed uplights equip with tiltable modules can tilt up to 30°. Its flexibility enables you to direct the light precisely where it's needed, enhancing the atmosphere and highlighting your favorite features

These fixtures are not only functional but also aesthetically pleasing, blending seamlessly into any design. With their robust construction and high-quality materials, they are built to withstand the elements while providing consistent performance. Whether you're illuminating pathways, accentuating architectural details, or creating a captivating outdoor ambiance, **Arcturus** recessed uplights are the perfect choice for both residential and commercial applications.

These lights are available in static colors, including RGB and RGBW. The fixtures can also be integrated with PWM or DMX controllers.

## Available on request

### CCT



### Beam Angle



### Control



### Body Finish



## Gallery



## Accessories



## Applications

- Architectual Buildings
- Facade Lighting
- Theme Parks
- Outdoor Landscaping
- Driveways & Walkways
- Indoor Accent Lighting
- Garden Features.
- Ambient Lighting